

MORSE 08B



This unit is designed for connecting to the COMPACT series ARDF transmitters. It brings significant improvement of code and timing options of the transmitters, useful for training purposes, foxoring competitions and promotion events.

Transmitting code, keying speed and timing schedule are widely adjustable.

FEATURES:

- **Operation continuous or in relations 5 min (30s/270s) or 2,5 min (30s/120s)**
- **Various transmitted codes**
- **Keying speed adjustable in 4 steps**
- **Supplied from the connected transmitter**
- **Small size (73x57x22 mm) and weight (40g)**
- **Rugged house**
- **Easy operation**

SPECIFICATIONS**GENERAL**

Supply: from the connected transmitter
Consumption: 5 mA

Operating temperature range: -10 ... + 60°C
Storage temperature range: -20 ... + 60°C

Covering: IP53
Dimensions: 57 (W) x 73(H) x 22 (D) mm
Weight: 40 g

LOGIC UNIT

Transmitted codes: MOE, MOI, MOS, MOH, MO5, MO, A ... Z
Keying speed: 35 – 50 – 70 – 100 PARIS
Timing schedules: 2,5- or 5-minute cycle, continuous operation
(30 s transmit, 120 or 270 s space)
Time base stability: better than 20 ppm (2s/day)